



TECHNICAL DATA SHEET

MOTORS LIVE 15W40

PRODUCT DESCRIPTION AND USE

15W40 is superior quality diesel engine oil produced with the perfect combination of additives being the product of modern technology and quality base oils. Totally fulfills its lubrication duty for natural aspiration or turbocharger diesel vehicles and construction equipment operated under heavy conditions. Also provides outstanding protection for high mileage vehicles.

FEATURES AND BENEFITS

- ✓ Protects the engine against abrasion during the first operation.
 - ✓ Enhanced additive system ensures the engine parts to remain cleaner and extends life of parts.
 - ✓ High thermal stability and minimizes formation of soot and residues.
- Specifically engineered to deliver longer oil life, enabling longer service intervals even under severe operating conditions.

TYPICAL PROPERTIES

Colour	ASTM D 6045	Yellow
Density@15°C, g/ml	ASTM D 4052	0,87-0,90
Viscosity@100°C, mm ² /s	ASTM D 445	12.5-16.3
Flash Point, °C	ASTM D 92	Min 220
Pour Point, °C	ASTM D 97	-24

*The above values may vary slightly according to production.

USER BENEFITS INCLUDE:

- Excels under high pressure: engine combustion pressures are increasing, which puts increased pressure on key engine parts.
- Performs at high temperature: engine oil is subjected to areas of very high temperature in modern engines, causing oxidation and oil thickening.